

## Fluke Networks 802.11a/b/g Wireless PC Card

Operating System	General Features							Supported Authentication for Active associations															
Operating System	Supported version (Previous versions or v 9.07)	Packet Capture	802.11n Capture (40 MHz)	31 Channel scanning - 5 GHz	Extended Channel- 5 GHz	Roaming Control for Survey tool	Noise detection	Open	WEP-128	LEAP-WEP	PEAP-WEP	EAP-TLS-WEP	EAP-FAST-WEP	LEAP-WPA	PEAP-WPA	EAP-TLS-WPA	EAP-FAST-WPA	LEAP-WPA2	PEAP-WPA2	EAP-TLS-WPA2	EAP-FAST-WPA2	WPA-PSK-TKIP	WPA2-PSK-AES
Windows XP with client utility	Client utility not supported																						
Windows XP with Windows Zero config (WLAN API Patch/SP3)	Previously supported	Supp	NS	Supp	NS	Supp	Supp	Supp	Supp	NS	Supp	NS	NS	NS	Supp	NS	NS	NS	Supp	NS	NS	Supp	Supp
Windows 7	Adapter not supported																						
Windows Vista	Adapter not supported																						

**NS: Not supported    Supp: Supported    Future:Future    NA: Not Applicable    PS: Partial Support**

Windows XP SP2 users: Download XP WLAN API Patch from : <http://www.microsoft.com/downloads/details.aspx?FamilyId=52A43BAB-DC4E-413F-AC71-158EFD1ADA50&displaylang=en>  
 Windows XP SP3 users: Do not install the Wireless LAN API Patch

**Notes for Windows XP with Windows Zero Config:**  
 Configure wireless profiles in Windows Zero Config  
 Adapter supported on Fluke Networks Optiview INA only