

Fluke Networks 802.11a/b/g/n Wireless PC Card

Operating System	General Features							Supported Authentication for Active associations															
	Supported version (Previous versions or v 9.0?)	Packet Capture	802.11n Capture (40 MHz)	31 Channel scanning - 5 GHz	Extended Channel- 5 GHz	Roaming Control for Survey tool	Noise detection	Open	WEP-128	LEAP-WEP	PEAP-WEP	EAP-TLS-WEP	EAP-FAST-WEP	LEAP-WPA	PEAP-WPA	EAP-TLS-WPA	EAP-FAST-WPA	LEAP-WPA2	PEAP-WPA2	EAP-TLS-WPA2	EAP-FAST-WPA2	WPA-PSK-TKIP	WPA2-PSK-AES
Windows XP with client utility	Client utility not supported																						
Windows XP with Windows Zero config (WLAN API Patch/SP3)	Previously supported	Supp	Supp	Supp	Supp	Supp	Supp	Supp	Supp	NS	Supp	Supp	NS	NS	Supp	Supp	NS	NS	Supp	Supp	NS	Supp	Supp
Windows 7 (not supported on INA)	Previously supported	Supp	Supp	Supp	Supp	Supp	Supp	Supp	Supp	NS	Supp	NS	NS	NS	Supp	NS	NS	NS	Supp	NS	NS	Supp	Supp
Windows Vista (not supported on INA)	Previously supported	Supp	Supp	Supp	Supp	Supp	Supp	Supp	Supp	NS	Supp	NS	NS	NS	Supp	NS	NS	NS	Supp	NS	NS	Supp	Supp

NS: Not supported Supp: Supported Future:Future NA: Not Applicable PS: Partial Support

Windows XP SP2 users: Download XP WLAN API Patch from : <http://www.microsoft.com/downloads/details.aspx?FamilyId=52A43BAB-DC4E-413F-AC71-158EFD1ADA50&displaylang=en>
 Windows XP SP3 users: Do not install the Wireless LAN API Patch

Notes

Configure wireless profiles in Windows Zero Config
 Adapter supported on Fluke Networks Optiview INA and PCs (refer to website for supported platforms)